

BELLEVILLE SPRING WASHERS

Guide to using tables

Outside Diameter

maximum size of outside diameter. If the spring is to be enclosed hole sizes must be greater than this dimension.

Thickness

of the Spring Section

Overall Height Unloaded

of a single spring washer

Price Group

reference to the price list

Calculated Load at Flat

load when the spring washer is fully compressed

Lee Stock Number

ordering reference.

Inside Diameter


minimum size of hole at centre. Mandrel sizes must be less than this dimension.

BELLEVILLE SPRING WASHERS
● Manufactured from 300 series stainless steel and passivated to ASTM A967

LEE STOCK NUMBER	INSIDE DIAMETER MINIMUM		OUTSIDE DIAMETER MAXIMUM		THICKNESS		OVERALL HEIGHT UNLOADED		CALCULATED LOAD AT FLAT	PRICE GROUP
	MM	IN	MM	IN	MM	IN	MM	IN		
093-005-188	2.25	0.093	4.78	0.188	0.13	0.005	0.36	0.014	25	5.7
093-006-188					0.15	0.006	0.38	0.015	44	9.8
093-007-188					0.18	0.007	0.36	0.014	54	12.2
093-009-188					0.23	0.009	0.36	0.014	82	18.4
093-010-188					0.25	0.010	0.38	0.015	113	25.3
115-005-250	3.18	0.125	6.35	0.250	0.20	0.008	0.41	0.016	52	11.8
138-010-281	3.51	0.138	7.14	0.281	0.25	0.010	0.51	0.020	100	22.6
138-013-281					0.33	0.013	0.53	0.021	176	39.7
138-015-281					0.38	0.015	0.58	0.023	271	60.9
148-015-281	3.76	0.148	7.14	0.281	0.38	0.015	0.61	0.024	318	71.4
156-009-312	3.96	0.156	7.92	0.312	0.23	0.009	0.51	0.020	66	14.8
156-010-312					0.25	0.010	0.51	0.020	82	18.5
156-011-312					0.28	0.011	0.55	0.022	116	26.1
156-015-312					0.38	0.015	0.58	0.023	222	49.9
156-017-312					0.43	0.017	0.64	0.025	323	72.6
187-012-375	4.75	0.187	9.53	0.375	0.30	0.012	0.61	0.024	118	26.5
187-015-375					0.38	0.015	0.64	0.025	192	43.1
187-017-375					0.43	0.017	0.66	0.026	251	56.5
187-020-375					0.51	0.020	0.74	0.029	409	92.0
187-022-375					0.56	0.022	0.76	0.030	484	108.8
187-030-375					0.76	0.030	0.91	0.036	921	206.9
187-020-562	4.75	0.187	14.27	0.562	0.48	0.020	0.94	0.037	307	69.0
187-028-562					0.71	0.028	1.07	0.042	694	156.0
218-020-437	5.54	0.218	11.10	0.437	0.51	0.020	0.81	0.032	402	90.3
218-023-437					0.58	0.023	0.86	0.034	560	125.9
218-035-687			17.45	0.687	0.86	0.035	1.27	0.050	969	217.7
250-017-500	6.35	0.250	12.70	0.500	0.43	0.017	0.74	0.029	189	42.4
250-018-500					0.46	0.018	0.76	0.030	224	50.4
250-020-500					0.51	0.020	0.81	0.032	307	69.1
250-023-500					0.58	0.023	0.91	0.036	506	113.8
250-024-500					0.61	0.024	0.97	0.038	620	139.3
250-025-500					0.64	0.025	0.99	0.039	700	157.4
250-038-500					0.97	0.038	1.19	0.047	1,581	355.3
250-042-562			14.27	0.562	1.07	0.042	1.40	0.055	2,314	520.0
250-052-687			17.45	0.687	1.32	0.052	1.75	0.069	3,653	820.9
250-025-750			19.05	0.750	0.64	0.025	1.24	0.049	476	106.9
250-052-750					1.32	0.052	1.65	0.065	2,319	521.1
250-070-937			23.80	0.937	1.78	0.070	2.54	0.100	8,316	1,868.9
312-024-625	7.92	0.312	15.88	0.625	0.61	0.024	1.02	0.040	453	101.8
312-030-625					0.76	0.030	1.12	0.044	774	173.9
312-031-625					0.76	0.031	1.22	0.048	1,037	233.0
312-047-674					1.19	0.047	1.50	0.059	1,732	387.2
					0.687	1.32	0.052	1.73		
					0.875	1.02	0.040	1.75		
					0.76	0.030	1.12	0.044		


ADDITIONAL INFORMATION

- 1 Our Belleville Spring Washers are manufactured from 300 series stainless steel and ASTM A967 (supercedes QQ-P-35)
- 2 A Belleville Spring Washer is a washer in the form of a cone, having constant material thickness, and used as a compression spring.
- 3 Unlike compression springs Belleville Spring Washers provide exceptionally high loads in restricted spaces.
- 4 Load flexibility can be varied by stacking the washers in various configurations (see below).
- 5 To minimise friction and optimise load ensure stacks of springs are guided over a shaft or in a cylinder.




FIVE IN SERIES

Series
Force is equal to that of a single spring washer. Deflection amounts to that of a single spring washer multiplied by the number used.



SIX IN PARALLEL

Parallel
Force is equal to that of a single spring washer multiplied by the number of stacked.



COMBINATION OF PARALLEL AND SERIES

Combination
Force is equal to that of a single spring multiplied by the number in each parallel series. Deflection is equal to a single spring washer multiplied by the number of series.